

SPECIFICATIONS

INDOOR

HOUSING

- Die Cast aluminium heat sink
- Architectural frames
- C-channel and flat hanger bars for tie down to ceiling grids
- Junction box is mounted on the frame for easy wiring , driver access for installation, and replacement

ELECTRICAL

- Quad Tap (QT) - 120/208/240/277V
- 50/60Hz
- 0-10V dimming standard
- Operating Temperature: -30°C (-22°F) - 40°C (104°F)

OPTICAL SYSTEM

- Up to 50,000 hours
- CRI \geq 80
- Offered in 30K, 35K, and 40K

CODE COMPLIANCE

- cULus Listed for Wet Locations (not suitable for coastal/sale water areas)
- Energy Star Listed
- RoHS Compliant
- Meets State of California Title 24

WARRANTY

- 5 Year
- 10 Year available

ORDERING INFORMATION

Trim Models

CATALOG #	WATTAGE	LUMENS	COLOR
ARCFK4-21L-QT-30K	21W	1,590	3000K
ARCFK4-28L-QT-40K	28W	1,940	4000K

Options (Factory Installed)

CATALOG #	
35K	- 3500K (special order)
EBCP-LED-5W	- 5W LED Emergency Ballast (600 Lumens)
EBCP-LED-8WW	- 7.8W LED Emergency Ballast (935 Lumens)
10YR	- 10 Year Warranty

Frame Models

CATALOG #	
ARCFK4-21L-FMK	- Frame for 21W Model
ARCFK4-28L-FMK	- Frame for 28W Model



Shown with trim and frame.
Ordered separately.

ARCFK4 4" LED Architectural Can & Frame-In Kit

