

SPECIFICATIONS

INDOOR

HOUSING

- Aluminum Housing
- Satin white powdercoat paint
- IC rated

ELECTRICAL

- Quad-Tap (120-277Vac)
- Operating Temperature: -20°C (-4°F) - 40°C (104°F)
- Wattage is field adjustable (present to 40W)
- 0-10V Dimmable driver stabard with built-in JBox

OPTICAL SYSTEM

- Acrylic Lens
- Backlit Illumination
- Uniform Illumination with no visible LED pixilation
- Color Tunable from 3500K,4000K, 5000K
- 50,000 hours @ L₇₀
- CRI > 80

MOUNTING

- Standard Mounting; recessed in grid ceilings
- Can be surface mounted

CODE COMPLIANCE

- cULus Listed for Damp Locations
- DLC Listed

WARRANTY

- 5 Year



FP12-K Color and Wattage Tunable Backlit Panel

	3500K	4000K	5000K
1X4-20W	2400 Lm	2600 Lm	2600 Lm
1X4-30W	3450 Lm	3700 Lm	3500 Lm
1X4-35W	3950 Lm	4200 Lm	4000 Lm
2X2-20W	2400 Lm	2600 Lm	2600 Lm
2X2-30W	3450 Lm	3700 Lm	3500 Lm
2X2-35W	3950 Lm	4200 Lm	4000 Lm
2X4-30W	3850 Lm	4200 Lm	3900 Lm
2X4-35W	4200 Lm	4550 Lm	4235 Lm
2X4-45W	5300 Lm	5650 Lm	5350 Lm

ORDERING INFORMATION

CATALOG #	Size	Wattage	Lumens	Color
FP12-K-14-1L-QT-MCT	1X4	20W/30W/35W	2400 - 4200 Lm	35K/40K/50K
FP12-K-22-1L-QT-MCT	2X2	20W/30W/35W	2400 - 4200 Lm	35K/40K/50K
FP12-K-24-1L-QT-MCT	2X4	30W/35W/45W	3900 - 5650 Lm	35K/40K/50K

OPTIONS

- EM - Emergency Battery