

SPECIFICATIONS

INDOOR

HOUSING

- Aluminum frame and steel housing backplate
- Available in 1X4, 2x2 and 2x4 models

ELECTRICAL

- Quad-Tap (120-277Vac)
- 0-10V Dimmable driver standard
- Operating Temperature: -10°C (14°F) - 40°C (104°F)

OPTICAL SYSTEM

- .100" Clear Acrylic lens standard
- MCT (field selectable between 35K/40K/50K)
- CRI > 80
- 50,000 hours @ L₇₀

MOUNTING

- Integrated clips for surface, suspended, or recessed mounting

CODE COMPLIANCE



- UL Listed for Wet Locations and insulated ceilings (Type IC-Rated)
- cETL/ETL Listed
- NSF Approved
- RoHS Compliant
- BAA Compliant

WARRANTY


- 5 Year




FP14-AEL LED Selectable NSF Panel



1x4



2x2



2x4

ORDERING INFORMATION

CATALOG #	Size	Wattage	Lumens	Color
FP14-AEL-14-1L-QT-MCT	1x4	20W - 40W	2200 - 4400 Lms	35K/40K/50K
FP14-AEL-22-1L-QT-MCT	2x2	20W - 40W	2600 - 5200 Lms	35K/40K/50K
FP14-AEL-24-1L-QT-MCT	2x4	30W - 72W	3900 - 9360 Lms	35K/40K/50K

OPTIONS (Factory Installed)

EM8W	- 8W LED Emergency Backup
EM14W	- 14W LED Emergency Backup
480V	- 347-480V Driver
CA125	- .125" Clear Acrylic
CL125	- .125" Clear Polycarbonate
CL187	- .187" Clear Polycarbonate
CP250	- .25" Clear Polycarbonate
CP375	- .375" Clear Polycarbonate

ACCESSORIES (Order Separately)

DWK24	- 2'x4' Gasketed drywall framing kit
DWK22M	- 2'x2' Gasketed drywall framing kit
DWK14	- 1'x4' Gasketed drywall framing kit
VWK24	- 2'x4' Vandal resistant gasketed drywall framing kit
VWK22	- 2'x2' Vandal resistant gasketed drywall framing kit
VWK14	- 1'x4' Vandal resistant gasketed drywall framing kit

	H (in)	W (in)	Dp (in)
1x4	11.9	47.7	1.77
2x2	23.7	23.7	1.77
2x4	23.7	47.7	1.77