

SPECIFICATIONS

HIGHBAYS

HOUSING

- Painted die-cast aluminum housing
- White housing

ELECTRICAL

- Quad Tap (QT): 120 - 277V
- 277-480V available
- 0-10V dimmable driver standard
- Operating Temperature: -40°C - 45°C (-40°F - 113°F)

OPTICAL SYSTEM

- Polycarbonat Lens
- CRI >80 standard
- Offered in 30K, 40K, and 50K
- 115° Beam angle

MOUNTING

- Mounting ring standard

CODE COMPLIANCE

- cULus Listed for Wet Locations
- IP66 Rated
- NSF Rated
- RoHS Compliant

WARRANTY

- 5 Year



HBFP3-F NSF Rated LED Highbay

ORDERING INFORMATION

MODEL#	Wattage / Lumens	Voltage	CCT	Trim
HBFP3-F	80AL (80W, 12,000 Lm)	QT (120-277V)	30K	Blank (White)
	80BL (80W, 15,200 Lm)	480V*(277-480V)	40K	BL (Blue)
	100AL (100W, 15,000 Lm)		50K	RD (Red)
	100BL (100W, 19,000 Lm)			BK (Black)
	150AL (150W, 22,500 Lm)			GN (Green)
	150BL (150W, 28,500 Lm)			
	200AL (200W, 30,000 Lm)			
	200BL (200W, 38,000 Lm)			

*480V only available with 100AL, 150AL, 200AL models

OPTIONS (Factory Installed)

- OCS - Occupancy Sensor

Ø17.08"

