

SPECIFICATIONS

HIGHBAYS

HOUSING

- Die cast aluminum housing and heatsink
- Black finish

ELECTRICAL

- Quad Tap (QT) - 120 - 277V
- 480V available
- 0-10V Dimmable driver standard
- 6kV surge protection standard

OPTICAL SYSTEM

- CRI >80
- Reflectors available
- Offered in selectable 40K or 50K, also available field selectable between 40K/50K
- 120° Beam angle

MOUNTING

- Hook mount standard
- Ring mount, pendant adapter, U-bracket also available

CODE COMPLIANCE

- cULus Listed for Wet Locations
- DLC Premium Listed

WARRANTY

- 5 Year



HBLE55-F Integrated Controls LED Highbay

ORDERING INFORMATION

MODEL#	Wattage / Lumens	Voltage	CCT	Mounting
HBLE55-F	100AL (100W, 15,000 Lm)	QT (120-277V)	40K	RG (Ring, standard)
	100BL (100W, 18,000 Lm)	480V (277-480V)	50K	HM (G-Hook)
	120AL (120W, 18,000 Lm)		MCT (40K/50K)	YM (U-Bracket)
	120BL (120W, 31,600 Lm)			PA (Pendant Adapter)
	150AL (150W, 22,500 Lm)			
	150BL (150W, 27,000 Lm)			
	200AL (200W, 30,000 Lm)			
	200BL (200W, 36,000 Lm)			
	240AL (240W, 36,000 Lm)			
	240BL (240W, 43,200 Lm)			
	310AL (310W, 46,500 Lm)			
	310BL (310W, 52,700 Lm)			
	1AL (100W/120W/150W: 15,000 - 22,500 Lm)			
	1BL (100W/120W/150W: 18,000 - 27,000 Lm)			
	2AL (180W/200W/240W: 27,000 - 36,000 Lm)			
	2BL (180W/200W/240W: 32,400 - 43,200 Lm)			
	3AL (240W/280W/310W: 36,000 - 46,500 Lm)			
	3BL (240W/280W/310W: 43,200 - 55,800 Lm)			

Options/Accessories on 2nd Page

OPTIONS / ACCESSORIES

OPTIONS (Factory Installed)

Controls

OCSD	- Daylight Sensor
MOCS	- Microwave Sensor
PIR	- PIR Sensor
WOCS	- Wireless Network Motion Sensor (Bluetooth)
WPIR	- Wireless Network PIR Sensor (Bluetooth)

Battery

EM	- Battery Backup
----	------------------

ACCESSORIES (Ships on Side)

HBLED55-F-PR1	- Polycarbonate Reflector (100W/120W/150W models)
HBLED55-F-PR2	- Polycarbonate Reflector (200W/240W/320W models)
HBLED55-F-AR1	- Aluminum Reflector (100W/120W/150W models)
HBLED55-F-AR2	- Aluminum Reflector (200W/240W/320W models)
HBLED55-F-REM	- Remote Controller

