

SPECIFICATIONS

HIGHBAYS

HOUSING

- Die-cast aluminum housing
- Foldable housing

ELECTRICAL

- Quad Tap (QT) - 120-277V
- 277-480V step-down transformer available
- 0-10V Dimmable driver standard
- Operating Temperature: -40°C (-40°F) - 40°C (104°F)
- 50,000 hours @ L₇₀
- THD < 15%
- PF > 0.9

OPTICAL SYSTEM

- Polycarbonate lens
- MCT (Selectable between 35K/40K/50K)
- CRI>80

MOUNTING

- V-Hooks and chain kit standard
- Cable Kits available

CODE COMPLIANCE

- cULus Listed for Damp Locations
- DLC Premium listed
- FCC Compliant
- RoHS Compliant

WARRANTY

- 5 Year



HBLED61-S-MCT

Color and Wattage
Foldable Highbay

ORDERING INFORMATION

CATALOG #	Description
HBLED61-S-2X1L-QT-MCT	2' - 80W / 110W / 135W (12000 / 16500 / 20250 Lm) Color Selectable
HBLED61-S-4X1L-QT-MCT	4' - 180W / 200W / 220W (27000 / 30000 / 33000 Lm) Color Selectable
HBLED61-S-4X2L-QT-MCT	4' - 290W / 320W / 350W (43500 / 48000 / 52500 Lm) Color Selectable

OPTIONS (Ships Installed)

EM13I	- Installed Internal Emergency Battery Backup (13W, 24' max height)
EM13E	- Installed External Emergency Battery Backup (13W, 24' max height)
EM25E	- Installed External Emergency Battery Backup (25W, 35' max height)
480V	- 277V - 480V Stepdown Transformer

ACCESSORIES (Ships on the Side)

ANT-6-4T	- Screw-in PIR On/Off Occupancy Sensor
ANT-5-AT	- Screw-in PIR Bi-Level Dimming Smart Sensor
HBLED61-S-PMB	- Pendant Mount Bracket
HBLED-S-RC	- Remote for Sensor
GK10-S	- 10' Aircraft Cables

2ft Models
24"L x 12"W x 4.5"H

4ft Models
48"L x 12"W x 4.5"H

ELECTRICAL INFORMATION

Catalog #	Input Amps (A)	
	120V	277V
HBLED61-S-2X1L (35K)	1.33	0.58
HBLED61-S-2X1L (40K)	1.47	0.64
HBLED61-S-2X1L (50K)	1.60	0.69
HBLED61-S-4X1L (35K)	1.65	0.71
HBLED61-S-4X1L (40K)	1.83	0.79
HBLED61-S-4X1L (50K)	2.02	0.87
HBLED61-S-4X2L (35K)	2.66	1.15
HBLED61-S-4X2L (40K)	2.93	1.27
HBLED61-S-4X2L (50K)	3.21	1.39