

SPECIFICATIONS

HAZARDOUS

HOUSING

- Heavy duty die cast aluminum housing
- Available in 2' and 4' models
- Powder coated finish
- Corrosion resistant housing and hardware

ELECTRICAL

- Quad Tap (QT) - 120-277V
- 480V available
- Dimmable driver available

OPTICAL SYSTEM

- Clear polycarbonate lens or Opal polycarbonate lenses available
- Available in 4000K and 5000K
- CRI \geq 70
- 85,000 Hours L_{70}
- Operating Temperature: -40°C - 60°C (-40°F - 140°F)

MOUNTING

- Surface and Pendant mounting standard
- Additional accessories available

CODE COMPLIANCE

- cETLus Listed
- Class I, Division II, Groups A, B, C, D
- Class II, Division I, Groups E, F, G
- Class II, Division II, Groups F, G
- Class III
- IP66 Rated
- RoHS Compliant
- Meets UL Requirements

WARRANTY

- 5 year warranty
- 10 year warranty optional



HLTN-F LED Hazardous Location Fixture

CATALOG #	Wattage	Length	
HLTN-F-2X20L-QT-*	20W	2ft.	2,000 - 2,800
HLTN-F-2X40L-QT-*	40W	2ft.	4,800 - 5,600
HLTN-F-4X20L-QT-*	20W	4ft.	2,000 - 2,800
HLTN-F-4X40L-QT-*	40W	4ft.	4,800 - 5,600
HLTN-F-4X60L-QT-*	60W	4ft.	7,200 - 8,400
HLTN-F-4X80L-QT-*	80W	4ft.	10,000 - 11,200

***Specify Color Temp: 30K, 40K, 50K, 60K**

OPTIONS (Ships Installed)

DIM	- Dimmable Driver
480V	- 277V - 480V
EBLED	- Integral Battery Backup
OCS	- Occupancy Sensor
BAA*	- Buy American Compliant
TAA*	- Trade Agreements Act Compliant

*Contact factory for availability

ACCESSORIES (Order separately, ships on side)

HLTN-F-JBOX	- Junction Box
HTN-F-FL	- Flat Lens