VersaLED Lighting

Versatile Lighting Solutions

Project

Type

Catalog Number

SPECIFICATIONS

MATERIAL

- Oval front-lighted, back projection mirror
- 24" W x 32" H (mounts only one way, W X H)
- 5mm polished glass, copper free
- Anodized aluminum frame, SS screws

DIMENSIONS

- Frame Depth: 1.50"
- Outside Frame Perimeter: 2.5" inside of mirror perimeter
- Frosted area 2"
- Mirrored area outside of frosted glass 2" wide

MOUNTING

- Frame has 4 integrated aluminum mounting brackets attached to the frame used to secure the frame to the wall.
- (4) Heavy duty screw-in wall anchors are included.
- (2) Mounting brackets installed on the rear of the mirror that slide into the cross-bars on the aluminum frame, allowing the mirror to be mounted after the frame has been installed

ILLUMINATION

- LED Strip: 40 LEDs per ft
- 4,654 Lumens
- 50,000 hours life expectancy
- 30.4W
- 6000K standard
- CRI: 92

ELECTRICAL

- 100-240VAC Input
- 12VDC Output
- Connects to standard switched lighting circuit

CODE COMPLIANCE

- cETLus Listed
- Meets UL Requirements

WARRANTY

- 5 Years





MM10 LED Mirror

ORDERING INFORMATION

CATALOG

MM10-31L-QT



