# VersaLED Lighting

Versatile Lighting Solutions

#### SPECIFICATIONS

#### MATERIAL

- Rectangular front-projecting, backlit mirror
- 72" W x 36" H (mounts only one way, W X H)
- 5mm polished glass, copper free
- Anodized aluminum frame, SS screws
- Switch provided

#### DIMENSIONS

- Frame Depth: 1.50"
- Frame Perimeter: 1.0" inside of mirror perimeter
- Inner frame perimeter approx 5.75" inside mirror perimeter
- Top mounting bar: 7.50" from top edge
- Frosted area 2"
- Mirrored area outside of frosted glass 2" wide

#### MOUNTING

- Frame has 4 integrated aluminum mounting brackets attached to the frame used to secure the frame to the wall.
- (4) Heavy duty screw-in wall anchors are included.
- (2) Mounting brackets installed on the rear of the mirror that slide into the cross-bars on the aluminum frame, allowing the mirror to be mounted after the frame has been installed

#### **ILLUMINATION**

- LED Strip: 40 LEDs per ft
- 12,907 Lumens
- 50,000 hours life expectancy
- 74W
- 6000K standard
- CRI: 92

#### **ELECTRICAL**

- 100-240VAC Input
- 12VDC Output

#### CODE COMPLIANCE

- cETLus Listed
- Meets UL Requirements

#### WARRANTY

- 5 Years

#### **Catalog Number**

Project

Type

**MULTI-FAMILY** 



## **MM21 LED Mirror**

### ORDERING INFORMATION

#### **CATALOG #**

MM21-74L-QT



