VersaLED Lighting

Versatile Lighting Solutions

SPECIFICATIONS

MATERIAL

- Rectangular front-projecting, backlit mirror
- 60" W x 36" H (mounts only one way, W X H)
- 5mm polished glass, copper free
- Anodized aluminum frame

DIMENSIONS

- Frame Depth: 1.25"
- Frame Perimeter: 2.5" inside of mirror perimeter
- Frame Width: 1.5"
- Top mounting bar: 5.25" from top edge

MOUNTING

- Frame has 4 integrated aluminum mounting brackets attached to the frame used to secure the frame to the wall.
- (4) Heavy duty screw-in wall anchors are included.
- (2) Mounting brackets installed on the rear of the mirror that slide into the cross-bars on the aluminum frame, allowing the mirror to be mounted after the frame has been installed

ILLUMINATION

- LED Strip: 40 LEDs per ft
- 6W per ft
- 12,320 Lumens
- 50,000 hours life expectancy
- 74.2W
- 6000K standard, 3000K available
- CRI: 92

ELECTRICAL

- 100-240V Input
- 12VDC Output

CODE COMPLIANCE

- cETLus
- Meets UL Requirements

WARRANTY

- 5 Years

Project

Type

Catalog Number



MULTI-FAMILY

MM6 LED Mirror

ORDERING INFORMATION

CATALOG #

MM6-74L-QT



