

SPECIFICATIONS

OUTDOOR

HOUSING

- Powder coated die-cast aluminum housing
- Bronze finish standard, also available in black, white, gray
- Fits 3" OD post
- For use with 2^{3/8"} Tenon Mount

ELECTRICAL

- Quad-Tap (120-277Vac)
- 480V Available
- 0-10V dimmable driver standard
- Operating Temperature: -4°F - 124°F (-20°F - 50°F)

OPTICAL SYSTEM

- Clear polycarbonate lens
- Lumen Range: 4,700 - 20,400
- Color Tuning between 3000K, 4000K, and 5000K (MCT)
- Type V Distribution standard; Type IV also available
- CRI > 80

CODE COMPLIANCE

- cULus Listed for Wet Locations
- IP65 Rated
- Title 24 Listed
- DLC Listed
- FCC Compliant
- RoHS Compliant

WARRANTY

- 5 Year



PT6-EN-MCT
LED Color and Wattage
Selectable Post Top

ORDERING INFORMATION

CATALOG #	Wattage	Lumens
PT6-EN-1L-QT-MCT	35W/ 50W/ 70W	4,700 / 7,000 / 10,200
PT6-EN-2L-QT-MCT	100W/ 125W/ 150W	13,900 / 17,400 / 20,400

OPTIONS (Ships Installed)

WH	- White Housing (bronze standard)
BK	- Black Housing (bronze standard)
GY	- Gray Housing (bronze standard)
480V	- 277V-480V (replaces QT in part number)
CC	- Custom Color
PC	- Photocell
OCS	- Bi-Level Motion Sensor
T4	- Type IV Distribution (type V standard)
EM	- Emergency Battery Backup

ACCESSORIES (Order Separately, Ships on Side)

3PR-EN	- 3-Pin Receptacle
3PRSC-EN	- 3-Pin Shorting Cap
7PR-EN	- 7-Pin Receptacle

