

SPECIFICATIONS

INDOOR

HOUSING

- Housing is die-formed steel
- Corrosion and scratch resistant
- Flush door with clam latches that hinges from either side
- Equipped with earthquake clips
- Easy access plate for quick wiring
- Available in 2x2 and 2x4 size housings

ELECTRICAL

- Quad Tap (QT) - 120/208/240/277V
- Dimmable driver standard
- 347-480V available

OPTICAL SYSTEM

- Frosted ribbed acrylic lens
- 50,000 hours @ L₇₀
- CRI >84
- Offered in 30K, 35K, 40K, 50K

CODE COMPLIANCE

- cETLus Listed
- Meets UL Requirements
- ARRA Compliant
- Meets DLC Requirements

WARRANTY

- 5 Year
- 10 Year Warranty available



RT6 LED Recessed Troffer

MODEL#	Size	Lumens
RT6-22X24L-QT-*	2X2	2,600 Lumens
RT6-22X28L-QT-*	2X2	3,000 Lumens
RT6-22X35L-QT-*	2X2	4,100 Lumens
RT6-24X35L-QT-*	2X4	3,650 Lumens
RT6-24X48L-QT-*	2X4	5,400 Lumens
RT6-24X52L-QT-*	2X4	5,125 Lumens
RT6-24X57L-QT-*	2X4	6,050 Lumens

*Specify Color; 30K, 35K, 40K, 50K

OPTIONS (Factory Installed)

EM5	- 5W EM Ballast (650 Lumens)
EM7	- 7W EM Ballast (900 Lumens)
EM10	- 10W EM Ballast (1300 Lumens)
WP6	- 6' 3-wire Whip
480V	- 347-480V Driver
OCS	- Integral Occupancy Sensor
10YR	- 10 Year Warranty

