

SPECIFICATIONS

MULTI-FAMILY

HOUSING

- Metal housing and trim
- Offered in 4" and 6"
- Round housing
- White Trim provided standard; black, bronze, and brushed nickel trims available

OPTICAL SYSTEM

- Frosted acrylic
- Tunable Downlight RGB+CW
- 50,000 hours @L₇₀
- CRI > 80
- Wattage and Lumens: 4" (9W, 600 lms); 6" (12W, 1000 lms)
- 2700K-6500K
- Beam Angle: 110°

ELECTRICAL

- 120V
- Operating temperature: -40°C (-40°F) - 45°C (114°F)

MOUNTING

- Tension clips mount into 1/2" - 1 1/2" thick ceiling
- Pre-wired junction box with circuit wiring built in

CODE COMPLIANCE

- cETLus Listed for Wet Locations
- Energy Star Rated
- Title24 Compliant
- FCC Compliant

WARRANTY

- 5 year warranty



SD9-CL Snap-In ColorLED Downlight

ORDERING INFORMATION

CATALOG#	Description
SD9-CL-4-9L-120V-MCT	9W, 600 Lms, 120V, 27K-65K, White Finish
SD9-CL-6-12L-120V-MCT	12W, 1000 Lms, 120V, 27K-65K, White Finish

Options (Factory Installed)

EM - Emergency Backup Battery

Accessories (Ships on Side)

SD9-TRM-#-*	- Trim
SD9-4-RI	- 4" Rough-In Plate (6 1/2" x 13 1/4")
SD9-6-RI	- 6" Rough-In Plate (8 1/2" x 17 1/4")
SD9-8-RI	- 8" Rough-In Plate (10 1/2" x 26")
SD9-URI	- Rough-In Plate (7" x 26")
SD9-PMP	- 2 3/4/6" Pre-Mounting Plate
SD9-GR-#	- Goof Ring

#Specify Size: 4, 6

*Specify Color: **BK-Black**, **BZ-Bronze**, **BN-Brushed Nickel**

