

## SPECIFICATIONS

OUTDOOR

### HOUSING

- Low-profile die-formed aluminum housing
- Available in bronze or white powdercoat finish
- Built-in sensor housing
- Knockouts for external-mount sensor and conduit entry

### ELECTRICAL

- Quad Tap (QT) - 120/208/240/277V
- Dimmable driver standard
- 347V and 480V Drivers available
- Operating Temperature: -40°C (-40°F) - 50°C (122°F)

### OPTICAL SYSTEM

- Molded acrylic optical lens
- Aluminum boards
- 219,000 hours @ L<sub>70</sub>
- CRI >80
- Power Factor > .9
- THD < 20%
- Type V
- Offered in 3000K, 4000K and 5000K

### ILLUMINATION

- 30W: 30W LED (34 system watts)
- 37W: 37W LED (43 system watts)
- 48W: 48W LED (55 system watts)
- 65W: 65W LED (75 system watts)

### MOUNTING

- Included easy-hang bracket fits standard 4" electrical box
- Quick-mount/Pendant bracket available

## ORDERING INFORMATION

CATALOG #	Wattage	Lumens	Color
VR19-Q-30L-QT-30K	34W	4,350	3000K
VR19-Q-30L-QT-40K	34W	4,526	4000K
VR19-Q-37L-QT-40K	43W	5,582	4000K
VR19-Q-48L-QT-40K	54W	7,242	4000K
VR19-Q-48L-QT-50K	54W	7,524	5000K
VR19-Q-65L-QT-40K	75W	9,807	4000K

## OPTIONS (Factory Installed)

WH	-	White Housing (Bronze standard)
EBLED	-	Battery Backup
SGP	-	Surge Protection
SGF	-	Single Fuse (120-277V only)
DBF	-	Double Fuse (120-277V only)
347V	-	347V Driver (30 and 37W models only)
480V	-	347-48
0V Driver	-	(30 and 37W models only)
PC3	-	120-277V Photocell
OCS	-	Microwave sensor with dimming for mounting heights of 8-40' (120-277V only)
OCS2	-	Microwave on/off motion sensor for mounting heights of 8-419' (120-277V only)
VRQM	-	Quick-mount/Pendant mount
10YR	-	10 Year Warranty
CC	-	Custom Color
USA	-	Assembled in USA

### CODE COMPLIANCE

- cSAus Listed Wet Location (Damp location with VRQM)
- Meets UL Requirements
- IP66 Rated
- Made in USA available
- Meets DLC Requirements

### WARRANTY

- 5 Year
- 10 Year Warranty available



## VR19-Q-LED Slim LED Canopy Light

