

## SPECIFICATIONS

OUTDOOR

### HOUSING

- Heavy duty die cast aluminum housing
- Textured architectural bronze powdercoat finish
- 1/2" Coin plugs with O-rings for Conduit
- Nickel-plated stainless steel hardware

### ELECTRICAL

- Quad Tap (QT) - 120/208/240/277V
- 0-10V Dimmable driver standard
- Operating Temperature: -40°C (-40°F)

### OPTICAL SYSTEM

- Polycarbonate lens
- 150,000 hours @ L<sub>70</sub>
- CRI >70
- Power Factor > .99

### MOUNTING

- Mounting plate on back for easy mounting

### CODE COMPLIANCE

- cULus Listed for Wet Locations
- Meets DLC Requirements

### WARRANTY

- 5 Year
- 10 Year Warranty available



## VR23-C Color and Wattage Selectable LED Canopy

CATALOG#	Wattage	Lumens	CCT
VR23-C-1L-QT-MCT	14W/26W/38W/43W	5,500	30K/40K/50K
VR23-C-2L-QT-MCT	18W/35W/52W/60W	7,707	30K/40K/50K
VR23-C-3L-QT-MCT	26W/49W/73W/83W	10,815	30K/40K/50K

### OPTIONS (Factory Installed)

EBLED	- 8W Integral Emergency Ballast
PC	- 120-277V Photocell
SGP	- 10kV Surge Protection
10YR	- 10 Year Warranty

