

SPECIFICATIONS

OUTDOOR

HOUSING

- Heavy duty die cast aluminum housing
- Textured architectural bronze powdercoat finish
- 1/2" Coin plugs with O-rings for Conduit
- Nickel-plated stainless steel hardware

ELECTRICAL

- QT Voltage: 100 - 277V
- 0-10V Dimmable driver standard
- Operating Temperature: -40°C (-40°F) - 54°C (130°F)

OPTICAL SYSTEM

- Polycarbonate lens
- 150,000 hours @ L₇₀
- CRI >80
- Power Factor > .99
- THD < 15%

MOUNTING

- Mounts directly over a 4" recessed outlet box, or 3/4" surface conduit

CODE COMPLIANCE

- UL Listed for Wet Locations
- IP67 Rated
- DLC Listed

WARRANTY

- 5 Year
- 10 Year Warranty available



VR7-T-LED Slim LED Canopy Light

CATALOG #	Wattage	Lumens
VR7-T-28L-QT-*	28W	3,484 - 3,584 Lm
VR7-T-40L-QT-*	40W	4,861 - 5,040 Lm
VR7-T-60L-QT-*	60W	7,474 - 7,800 Lm
VR7-T-90L-QT-*	90W	11,366 - 11,880 Lm

*Specify: **30K, 40K, 50K**

OPTIONS (Factory Installed)

EM8	- 8W Emergency Battery
EM15	- 15W Emergency Battery
EM20	- 20W Emergency Battery
OCS	- Occupancy Sensor
PEN	- Pendant Adapter
10YR	- 10 Year Warranty

