

SPECIFICATIONS

INDOOR

HOUSING

- Die-formed cold rolled steel housing
- Nominal 9" width with a shallow design
- Corrosion and scratch resistant
- Diffuser self-aligns and hinges from either side for easy maintenance
- Available in 2' and 4' housings
- Surface, stem or chain mountable

ELECTRICAL

- Quad Tap (QT) - 120/208/240/277V
- Dimmable driver standard
- 347-480V driver available

OPTICAL SYSTEM

- Clear acrylic diffuser with prismatic bottom and ribbed linear sides
- Frosted lens available
- CRI >82
- Offered in 30K, 35K, 40K, 50K

MOUNTING

- Can be surface, stem, or chain mounted
- Single or continuous row mounting capability

CODE COMPLIANCE

- cETLus Listed
- Meets UL Requirements
- RoHS Compliant
- ARRA Compliant
- Meets DLC Requirements

WARRANTY

- 5 Year
- 10 Year Warranty available

ORDERING INFORMATION

MODEL#	Length / Lumens
WA4-2x12L-QT-*	2' - 1,665 Lumens
WA4-2x18L-QT-*	2' - 2,420 Lumens
WA4-2x24L-QT-*	2' - 3,135 Lumens
WA4-2x28L-QT-*	2' - 3,465 Lumens
WA4-2x30L-QT-*	2' - 3,630 Lumens
WA4-4x23L-QT-*	4' - 2,650 Lumens
WA4-4x32L-QT-*	4' - 3,450 Lumens
WA4-4x35L-QT-*	4' - 3,800 Lumens
WA4-4x48L-QT-*	4' - 5,100 Lumens
WA4-4x56L-QT-*	4' - 6,000 Lumens
WA4-4x72L-QT-*	4' - 8,200 Lumens

Specify 30K, 35K, 40K, or 50K

OPTIONS (Factory Installed)

FL	- Frosted Lens
EM5	- LED EM Ballast (5W, 850 Lumens)
EM7	- LED EM Ballast (7W, 1300 Lumens)
EM10	- LED EM Ballast (10W, 1700 Lumens)
CS6	- 18/3 6' Cordset
WP6	- 6', 3-Wire Whip
10YR	- Ten Year Warranty



WA4-LED LED Wraparound

